CFOS Gas Stick

Cleaned for Oxygen Grade Service

GAS STICK PART NUMBER MATRIX [1]

G2 A - 04 04 C - 1 - 0 0

Gas Stick

G2 = Regulator & Gauge w/ Mini Ball Valve

G3 = Regulator & Gauge Only

Regulator Size [2]

A = 0.15 Cv

B = 1.8 Cv

Inlet Size [3]

04 = 1/4"

06 = 3/8"

08 = 1/2"

12 = 3/4"

Outlet Size

04 = 1/4"

06 = 3/8"

08 = 1/2"

12 = 3/4"

Outlet Filter Option (0.003 µM)

0 = Not Required

1 = TEM Filter (low flow)

2 = TEM Filter (high flow)

3 = Entegris Filter

Lockout and Mounting Bracket Options

0 = Not Required

1 = Mounting Bracket (Strut Channel Compatible)

2 = Valve Lockout

3 = Valve Lockout and Mounting Bracket

Gauge

1 = -30inHg-160 psig

Connection Type [4]

C = Compression in, Compression out

T=Tube in, Compression out

[1] Not all possible part number configurations are available. Please contact Valex for availability.

[2] Regulator Sizing: Typically .15 Cv is used for 1/4" gas sticks, while 1.8 Cv is used for 3/8" & 1/2" gas sticks.

[3] G3 Inlet Sizes: only offered in 1/4" and 1/2".

[4] Connection Types (available): G2 sticks (Option "C"), G3 (Option "T")